



MAGNELIS®

QUALITY	ZINC COATING (ZM)	THICKNESS (MM)	WIDTH (MM)
DX51D	ZM90 → ZM430 (ZM800*)	0,45 → 6*	25 → 1575*
DX52D	ZM90 → ZM430 (ZM800*)	0,45 → 6*	25 → 1575*
DX53D	ZM90 → ZM430 (ZM800*)	0,45 → 6*	25 → 1575*
DX54D	ZM90 → ZM430 (ZM800*)	0,45 → 6*	25 → 1575*
DX56D	ZM90 → ZM430 (ZM800*)	0,45 → 6*	25 → 1575*
S220GD	ZM90 → ZM430 (ZM800*)	0,45 → 6*	25 → 1575*
S250GD	ZM90 → ZM430 (ZM800*)	0,45 → 6*	25 → 1575*
S320GD	ZM90 → ZM430 (ZM800*)	0,45 → 6*	25 → 1575*
S350GD	ZM90 → ZM430 (ZM800*)	0,45 → 6*	25 → 1575*
S390GD	ZM90 → ZM430 (ZM800*)	0,45 → 6*	25 → 1575*
S420GD	ZM90 → ZM430 (ZM800*)	0,45 → 6*	25 → 1575*
S450GD (HYPER)	ZM90 → ZM430 (ZM800*)	0,45 → 6*	25 → 1575*
S550GD (HYPER)	ZM90 → ZM430 (ZM800*)	0,45 → 6*	25 → 1575*
HX300LAD	ZM90 → ZM430 (ZM800*)	0,45 → 6*	25 → 1575*
HX340LAD	ZM90 → ZM430 (ZM800*)	0,45 → 6*	25 → 1575*
HX420LAD	ZM90 → ZM430 (ZM800*)	0,45 → 6*	25 → 1575*
HX460LAD	ZM90 → ZM430 (ZM800*)	0,45 → 6*	25 → 1575*
HX500LAD	ZM90 → ZM430 (ZM800*)	0,45 → 6*	25 → 1575*



**TRUSTWORTHY
PARTNER**



**SUSTAINABLE
APPROACH**



**FLEXIBLE
DELIVERY**



HOT ROLLED PICKLED

QUALITY	THICKNESS (MM)	WIDTH (MM)
DD11+B	1,5 → 8*	25 → 1575*
DD12+B	1,5 → 8*	25 → 1575*
DD13+B	1,5 → 8*	25 → 1575*
DD14+B	1,5 → 8*	25 → 1575*
S235JR+B	1,5 → 7*	25 → 1575*
S275JR+B	1,5 → 8*	25 → 1575*
S355JR+B	1,5 → 8*	25 → 1575*
S315MC+B	1,5 → 8*	25 → 1575*
S355MC+B	1,5 → 8*	25 → 1575*
S390MC+B	1,5 → 6*	25 → 1575*
S420MC+B	1,5 → 6*	25 → 1575*
S460MC+B	1,5 → 6*	25 → 1575*
S500MC+B	1,5 → 6*	25 → 1575*

GALVINIZED (SENDZIMIR)

QUALITY	ZINC COATING (ZM)	THICKNESS (MM)	WIDTH (MM)
S250GD	Z275	1.5*	25 → 1500*
S250GD	Z275	2*	25 → 1500*
S250GD	Z275	2.5*	25 → 1500*
S250GD	Z275	3*	25 → 1500*
S350GD	Z275	1.5*	25 → 1500*
S350GD	Z275	1.75*	25 → 1500*
S350GD	Z275	2*	25 → 1500*
S350GD	Z275	2.5*	25 → 1500*
S350GD	Z275	3*	25 → 1500*
S350GD	Z275	4*	25 → 1500*