

VDE WRENCHES AND SOCKETS



► VDE open-end wrench

Chrome vanadium, chrome-plated, according to DIN 7446, jaw position 15°
Two-colour multilayer dip insulation, 1000 V

Art.-No.	WAF	Weight in g	1000 V
16-501 VDE	6	24	
16-502 VDE	7	25	
16-503 VDE	8	26	
16-504 VDE	9	38	
16-505 VDE	10	42	
16-506 VDE	11	48	
16-507 VDE	12	58	
16-508 VDE	13	68	
16-509 VDE	14	75	
16-511 VDE	15	88	
16-512 VDE	17	120	
16-513 VDE	19	160	
16-514 VDE	21	210	
16-515 VDE	24	300	
16-517 VDE	26	340	



► VDE single-ended ring wrench

Chrome vanadium, chrome-plated, according to DIN 7447,
Two-colour multilayer dip insulation, 1000 V

Art.-No.	WAF	Weight in g	1000 V
16-533 VDE	8	65	
16-535 VDE	10	80	
16-536 VDE	11	100	
16-537 VDE	12	110	
16-538 VDE	13	120	
16-539 VDE	14	150	
16-541 VDE	15	155	
16-542 VDE	16	170	
16-543 VDE	17	180	
16-544 VDE	18	240	



► VDE sockets

Chrome vanadium, chrome-plated, according to DIN 7448 qith square drive,
Two-colour multilayer dip insulation

Art.-No.	Inch	WAF	Weight in g	1000 V
16-441 VDE	1/2	10	60	
16-442 VDE	1/2	11	63	
16-443 VDE	1/2	12	64	
16-444 VDE	1/2	13	64	
16-445 VDE	1/2	14	67	
16-446 VDE	1/2	15	68	
16-447 VDE	1/2	17	74	
16-448 VDE	1/2	19	83	
16-449 VDE	1/2	22	114	
16-451 VDE	1/2	24	117	
16-452 VDE	1/2	27	181	
16-453 VDE	1/2	30	195	
16-454 VDE	1/2	32	200	
16-482 VDE	3/8	7	28	
16-483 VDE	3/8	8	29	
16-484 VDE	3/8	9	31	
16-485 VDE	3/8	10	31	
16-486 VDE	3/8	11	33	
16-487 VDE	3/8	12	33	
16-488 VDE	3/8	13	34	
16-489 VDE	3/8	14	36	
16-491 VDE	3/8	15	44	
16-492 VDE	3/8	16	50	
16-493 VDE	3/8	17	54	
16-494 VDE	3/8	19	58	
16-495 VDE	3/8	19	70	
16-496 VDE	3/8	20	72	
16-497 VDE	3/8	21	77	
16-498 VDE	3/8	22	94	

► VDE reversible ratchet

According to DIN 7449, two-colour multilayer dip insulation
Hold or release the inserts at the push of a button; right/left by turning the lever.

Art.-No.	Type	Total length	Weight in g	1000 V
16-471 VDE	1/2" square drive	260	668	
16-472 VDE	3/8" square drive	200	356	



16-471 VDE

► VDE T-Socket wrench

DIN 7436,, two-color multilayer immersion insulation insulated, with locking device

Art.-Nr.	Type	Total length	Weight in g	1000 V
16-475-VDE	1/2" 4-kt. Drive	20.5 x 14.5	453	



16-475-VDE

► Extension

DIN 7434, two-colour multilayer dip insulation
Cannulated, locking with screw, with locking device

Art.-No.	Type	Total length	Weight in g	1000 V
16-476 VDE	1/2" square drive	125	206	
16-478 VDE	3/8" square drive	125	154	



16-476 VDE

- other dimensions on request -
(minimum purchase 5 pieces)