

GEOMETRIC TWEEZERS

Every imaginable shape is possible. Bulbous or long, hollow tweezers with the appropriate diameter are suitable for the easy removal or insertion of round or cubic component parts. PVC dip-insulation on the tips protect sensitive parts made from plastic or glass such as laser optics or other opto-mechanical components.

Made from quality steel (nickel-plated, not anti-magnetic) or made from Stainless steel (anti-magnetic, non-corrosive and acid-resistant, non-reflective and matt-polished). The dissipative ESD coating provides a bleeder resistance of 10^6 - 10^9 ohms. Tweezers with ESD coating end with -13 in the article number.

Additional models with dissipative ESD coating on request.

The following types are available, specifications in mm:

Art.-No.	Art.-No.	Icon	Shape	A	B	C	D	E	Ai	Angle	Ø	Material	Total length	Weight in g
2-601	2-601-13	PIC1	-		8.2	6	3.2		20			steel nickel-plated	125	21
2-601-5		PIC1			9	8.5	4.7		26.5			steel nickel-plated*	125	21
2-601-7		PIC1	-		8.2	7	3.2		20			stainless steel	125	21
5-006		PDG3	64	14	5.6				25		5	steel nickel-plated	125	21
5-006-7	5-006-7-13	PDG3	64	13.5	5.8						5	stainless steel	125	23
5-007	5-007-13	PDG2	62	6.5	6				21		5	steel nickel-plated*	145	23
5-007-5		PDG2	62	7	6.2				21		5	steel nickel-plated	145	22
5-008		PDG4	67	11.5	5.9	8						steel nickel-plated	145	22
5-009		PFG2	68	13	6	3			25			steel nickel-plated*	145	25
5-013-7	5-013-7-13	PDG1	63		5			16		45°	1.5	stainless steel	125	15
5-014-7	5-014-7-13	PDG2	52	5	4				14		3.5	stainless steel	120	15
5-015-7	5-015-7-13	PDG2	53	8.8	3.5				14		6.5	stainless steel	120	15
5-016-7	5-016-7-13	PDG3	55	10.5	3.1						2	stainless steel	125	15
5-062	5-062-13	PDB1	59	2.3	1.5					35°	0.8	stainless steel	115	16
5-063	5-063-13	PDB1	58	2.3	3					35°	0.8	stainless steel	115	16
5-064	5-064-13	PDG2	54	2.3	1.5						0.8	stainless steel	120	16
5-065	5-065-13	PDG2	50	2.3	3						0.8	stainless steel	120	16
5-066	5-066-13	PNB4	8b	12	2.5					30°		stainless steel	120	15
5-067	5-067-13	PNB3	12	2.5	1					45°		stainless steel	120	15
5-068	5-068-13	PNG6	13		2.5					40°		stainless steel	120	13
5-114-7	5-114-7-13	PCU1	61	13	6	5.5					11	stainless steel	145	23

*tips PVC insulated

