

► 2-620

PLCC-extractor

For work on circuit boards (PCB) for easy excavation of parts and components
enables removal of integrated circuits, safe removal without the risk of damaging the pins
material: plastic and metal compound, length 100 mm, weight 21 g



► 2-161

Scriber, magnetic lifter with telescopic slide-out

Slim, elegant design, max. lifting force 0.025 kg, needle Ø 7 mm, extra hardened
for small, light metallic objects in hard-to-reach places pen shape with clip
for carrying in the breast pocket, telescopic rod max. 655 mm
Total length 145 mm, weight 34 g



► 2-800

Miniature tap and die set 30 pcs (M1.0 - M2.5 mm)

18 taps, each with a pre-cutter and a finish cutter
each 2 x hand taps (HGB) each M 1.0 - M 1.1 - M 1.2 - M 1.4 - M 1.6 - M 1.8 - M 2.0 - M 2.2 - 2.5
each 1 x dies M 1.0 - M 1.1 - M 1.2 - M 1.4 - M 1.6 - M 1.8 - M 2.0 - M 2.2 - M 2.5
1 x die holder
2 x tap wrenches
2 matching reducing rings
high speed quality steel (HSS) polished
in a practical storage box, measures 150 x 85 x 15 mm, weight 199 g



DESOLDERING SUCTION PUMPS

► 8-390

Desoldering suction pump PRAKTIK Ø 20 mm RD-7376

handy device in all-metal housing
high suction power due to 2-fold sealing of the piston
length 200 mm, weight 71 g



► 8-238

SMD vacuum pipette Vampir

for simple, safe and precise handling of SMD components,
angled suction nozzle and 3 suction cups 4, 6 and 9 mm (conductive)
length 150 mm, weight 60 g



GAS SOLDERING IRON

► 8-376

Gas soldering iron, works with butane lighter gas

operating time 45 minutes, Ignition with piezo-electronic system
soldering tip width 2 mm, tip temperature up to soldering: 580°C/1075°F
blow torch: 1300°C/2372°F, hot air tip 625°C/1157°F, hot knife 580°C/1075°F
75 wattage, TUV approval, length 170 mm, weight 94 g



Perfect for all mobile applications. The soldering iron is ignited by a piezo-electronic system.
The on/off switch is marked with 1-0, the ignition switch is marked with a lightning. Soldering, hot air or hot knife by the placement of different soldering tips possible.
Please note the enclosed instructions for use.