

► **3-0611**
Crimping pliers for BNC and TNC coaxial connectors

For BNC and TNC coaxial connectors, with ratchet lock and automatic release, suitable for internal contacts and external receptacles. Tool steel (HRC 54 - 56), surface burnished, Pressing range: hexagon socket for all inner contacts. Crimp length 2.3 mm inner-Ø (0.068 inch) 1.73 mm. Small hex for RG 58 crimp length 10.0 mm inner-Ø (0.213 inch) 5.41 mm. Middle hex for RG 59/62 crimp length 10.0 mm inner-Ø (0.256 inch) 6.50 mm. Large hex for RG 6 crimp length 10.0 mm inner-Ø (0.319 inch) 8.10 mm.

Total lenght: 200 mm, Weight: 520 g



3-0611

► **3-0611-00**
Ersatzmesser für 3-0611 (Paar)

Blades made of special stainless steel
Weight: 260 g



3-06011-00

► **3-0612**
Automatic crimping pliers

Automatic crimping pliers ratchet mechanism for crimping insulated terminals. version: 0.5 - 1.0 / 1.5 - 2.5 / 4 - 6 mm² (AWG 22 - 18 / 16 - 14 / 12 - 10) tool steel (HRC 54 - 56), surface burnished

Total lenght: 200 mm, Weight: 520 g



3-0612

► **3-871-6**
Pressing pliers 155 mm for wire 0.25 - 2.5 mm²

Crimping pliers, for wire end ferrules combined with wire cutters and stripping frames, for various wire thicknesses, for wire end ferrules from 0.25 - 2.5 mm² carbon steel. surface matt chrome plated, high-quality steel (HRC 54 - 56), handle dipped insulation, non-slip

Total lenght: 155 mm, Weight: 165 g



3-871-6

► **3-875-6**
Pressing pliers 255 mm for wire 0.5 - 16.0 mm²

Crimping pliers, for wire end ferrules combined with wire cutters and stripping frames, for various wire thicknesses, for wire end ferrules from 0.50 - 16.0 mm² carbon steel. surface matt chrome plated, high-quality steel (HRC 54 - 56), handle dipped insulation, non-slip

Total lenght: 226 mm, Weight: 285 g



3-875-6