








ROBUST PLIERS






Material Q & T steel according to DIN
Cutting edges inductively hardened

The following types are available, specifications in mm:

Art.-No.	Short description	Type	Flush	Cutting values				Head width	Cutting/ jaw length	Total length mm	Weight in g
				○	⊗	●	Ⓟ				
3-235-16	Telephone pliers	serrated jaws	–	–	–	–	–	15	55	160	145
3-245-16	Telephone pliers	serrated jaws	–	–	–	–	–	18	75	205	210
3-255-16	Telephone pliers	serrated jaws	–	–	–	–	–	18	70	205	210
3-531-16	Flat nose pliers	serrated jaws	–	–	–	–	–	15	40	150	105
3-132-16	Side cutters	–	Full flush	4.0	2.3	1.5	–	15	16	130	125
3-133-16	Side cutters	–	–	4.0	2.5	1.8	–	18	18	150	155
3-732-16	Combination pliers	serrated jaws	–	4.0	2.5	2.0	–	23	35	170	205



The pliers of this program have been successfully tested by several testing laboratories according to DIN EN 61340-5-1, 61340-2-1, as well as 61340-2-3 for work in ESD-protected areas.



The following types are available, specifications in mm:

Art.-No.	Short description	Type	Flush	Cutting values				Head width	Cutting/ jaw length	Total length mm	Weight in g
				○	⊗	●	Ⓟ				
3-133-13	ESD side cutters	–	Semi flush	4.0	2.5	1.8	–	18	18	145	165
3-245-13	ESD telephone pliers	serrated jaws	Semi flush	–	–	–	–	18	75	200	180
3-732-13	ESD combination pliers	serrated jaws	Semi flush	4.0	2.5	1.8	–	23	35	165	185