








► Watchmaker screwdriver magazine 6 pcs.

Material tool steel HRC 58-61

Metal handle with rotating cap (nickel-plated), for opening with blades inside

Weight: 33 g

| Art. No. | 4-392 | 4-393 |
|--|-------|-------|
|  Slot 1,5 mm | ✓ | ✓ |
|  Slot 2,0 mm | ✓ | ✓ |
|  Slot 2,5 mm | ✓ | ✓ |
|  Slot 3,0 mm | ✓ | ✓ |
|  Cross recess PH0 | ✓ | |
|  Cross recess PH00 | | ✓ |
|  Cross recess PH000 | | ✓ |



4-392, 4-393

MICRO SCREWDRIVER

Fine screwdrivers are also called micro screwdrivers and are used in precision mechanics for small screw sizes or miniature screws. The hard precision blade made of quality tool steel enables direct gripping of the miniature screw and provides optimum force closure. The sturdy plastic handle with rotation cap fits comfortably in the hand, the coloured ring facilitates work by quickly recognising the required size.

Blade (HRC 58-61) material molybdenum-vanadium steel, burnished black, handle plastic. 100% Made in Germany.













Instructions: High humidity or touching burnished blades with your fingers (sweat) causes flash rust. Therefore, the blades should always be kept dry or rubbed with a drop of oil for storage. If such rust forms on the blade, it can be easily removed, with a slight ground.

Blades are burnished to prevent the chrome from flaking off and to achieve absolute top dimensional stability.



4-380-14

The following types are available, specifications in mm:

| | Art.-No. | Symbol | Size / drive | Blade length | Blade width | Blade thickness | Blade diameter | Handle length | Total length | Weight in g |
|-----|----------|---|--------------|--------------|-------------|-----------------|----------------|---------------|--------------|-------------|
| NEW | 4-380-06 |  | Slot | 17 | 0.6 | 0.15 | 2.0 | 87 | 104 | 4 |
| NEW | 4-380-08 |  | Slot | 17 | 0.8 | 0.19 | 2.0 | 87 | 104 | 4 |
| | 4-380-10 |  | Slot | 17 | 1.0 | 0.20 | 2.0 | 87 | 104 | 4 |
| NEW | 4-380-12 |  | Slot | 17 | 1.2 | 0.25 | 2.0 | 87 | 104 | 4 |
| | 4-380-14 |  | Slot | 17 | 1.4 | 0.25 | 2.0 | 87 | 104 | 4 |
| | 4-380-18 |  | Slot | 17 | 1.8 | 0.30 | 2.0 | 87 | 104 | 4 |
| NEW | 4-380-20 |  | Slot | 17 | 2.0 | 0.40 | 2.0 | 87 | 104 | 4 |
| | 4-380-23 |  | Slot | 17 | 2.3 | 0.40 | 2.5 | 87 | 104 | 4 |
| NEW | 4-380-25 |  | Slot | 17 | 2.5 | 0.40 | 2.5 | 87 | 104 | 4 |
| | 4-380-30 |  | Slot | 17 | 3.0 | 0.50 | 2.5 | 87 | 104 | 4 |
| NEW | 4-380-90 |  | PH1 | 17 | - | - | 2.5 | 87 | 104 | 4 |
| NEW | 4-380-91 |  | PH0 | 17 | - | - | 2.5 | 87 | 104 | 4 |
| NEW | 4-380-92 |  | PH00 | 17 | - | - | 2.5 | 87 | 104 | 4 |
| NEW | 4-380-93 |  | PH000 | 17 | - | - | 2.0 | 87 | 104 | 4 |
| NEW | 4-380-94 |  | PH0000 | 17 | - | - | 2.0 | 87 | 104 | 4 |