

DELICATE TWEEZERS

STAINLESS STEEL

MINI 85 mm
OC

5-071

WITH ESD COATING

MINI 85 mm
OC

5-071-13

STAINLESS STEEL

PSF

5-078

WITH ESD COATING

PSF

5-078-13

3c

5-072

3c

5-072-13

MM

5-083

MM

5-083-13

SS

5-073

SS

5-073-13

SSBB

5-085

SSBB

5-085-13

1

5-074

1

5-074-13

MINI 90 mm
H

5-086

MINI 90 mm
H

5-086-13

BB

5-075

BB

5-075-13

MINI 90 mm
H

5-086-135

00

5-076

00

5-076-13

AC

5-087

AC

5-087-13

AA

5-077

AA

5-077-13

DELICATE TWEEZERS

Made from anti-magnetic, non-corrosive and acid-resistant stainless steel – non-reflective and matt-polished. The dissipative ESD coating provides a bleeder resistance of 10^6 – 10^9 ohm. Tweezers with ESD coating end with -13 in the article number.

The following types are available, specifications in mm:

Art.-No.	Art.-No. 	Icon	Shape	A	B	C	D	Angle	Tolerance (or acc. ISO2768)	Total length	Weight in g
5-071	5-071-13	PNG1	OC	48	0.2	0.4			0.3	85	8
5-072	5-072-13	PNG1	3c	46	0.3	0.4			0.2	110	11
5-073	5-073-13	PNG1	SS	53	0.2	0.4			0.3	140	13
5-074	5-074-13	PNG1	1	42	0.3	0.4			0.2	120	14
5-075	5-075-13	PNG3	BB	8	0.2					140	13
5-076	5-076-13	PNG1	00	46	0.5	1			0.4	120	19
5-077	5-077-13	PNG1	AA	50	0.3	0.6			0.3	130	16
5-078	5-078-13	PNG1	PSF	50	1	0.5			0.3	130	20
5-083	5-083-13	PNG1	MM	68	0.6	1			0.5	140	8
5-085	5-085-13	PTB1	SSBB	20	4.5			30°		140	14
5-086	5-086-13	PNG1	H	12	0.2	0.4			0.4	90	12
	5-086-135	PNG1	H	12	0.5	1.9				90	12
5-087	5-087-13	PNG1	AC	60	0.2	0.4			0.2	110	18

DELICATE TWEEZERS SETS

► SMD tweezers set 6 pcs

Content: 5-049, 5-053, 5-055, 5-059, 5-078, 5-089

Art.-No.	Description	Weight in g
5-050-A	in a pocket (synthetic leather)	135
5-050-ANY	in a pocket (nylon)	110
5-050-AES	without a pocket (loosely packed)	90
5-050-AV	with VARIO tool holder (5-090-1)	480

► ESD SMD tweezers set 6 pcs

Content: 5-071-13, 5-077-13, 5-191, 5-052-13, 5-861-13, 5-863-13

Art.-No.	Description	Weight in g
5-060-A	in a pocket (synthetic leather)	135
5-060-ANY	in a pocket (nylon)	110
5-060-AES	without a pocket (loosely packed)	90
5-060-AV	with VARIO tool holder (5-090-0)	480

ESD TWEEZERS WITH ESD DISSIPATIVE PVC DIP INSULATION (NON-SLIP)

ESD coating achieves a discharge resistance of 10^6 - 10^9 Ohm. PVC insulation enables optimal positioning due to slight adhesion to the tip.

A secure hold for small parts and components that slip away quickly, also suitable for securely holding glass lenses and optics.

Do you need a different shape with dissipative PVC insulation? Please do not hesitate to contact us.

