

## GROUNDING-, EARTH BONDING POINT


EPA suitable. For working in electrostatically protected areas (ESD workplace / ESD protection zone).



### ► 9-359-1

#### ESD earth bonding plug 3 x 10 mm with cable and eyelet

- EPB earth bonding point
  - for table screw connection, angled (incl. 2 screws)
  - as a ground connection point for personal grounding
  - cable length 2 m with 4 mm loop
  - 3 x 1 megaohm safety resistance, 10 mm press buttons
- Weight: 45 g



### ► 9-359-2

#### ESD earth bonding plug 2 x 1 MOhm and M5 connection

- EPB earth bonding point
  - Earthing plug with cable for EU sockets
  - as a ground connection point for personal grounding
  - ESD earth bonding plug 2 x 1 megaohm and M5 connection, 10 mm press buttons
  - 1x screw connection M5 for 4 mm eyelet
  - suitable cable: 9-343-1, 9-344-1
- Weight: 33 g



### ► 9-353

#### ESD crocodile clip 1 x 10 mm

- with banana plug socket, 10mm press button
  - press buttons 10 mm
- Weight: 18 g



### ► 9-343-1

#### ESD grounding cable 2 x 10 mm connection

- for connection between table and floor coverings and for connection to an earth potential.
  - with 1 megaohm safety resistance
  - 2 press buttons 10 mm for mats or floor connection
  - cable length 1.8 m
- Weight: 40 g



### ► 9-344-1

#### ESD grounding cable 1 x 10 mm with eyelet 4 mm


- for connection between table and floor coverings and for connection to an earth potential
  - with 1 megaohm safety resistance
  - 1 flat press button 10 mm for mats or floor connection
  - 1 eyelet for M5 thread at the socket ground
  - cable length 1.8 m
- Weight: 40 g



### ► SETS



9-205-ESD-SET1



9-215-ESD-SET1



9-251-ESD-SET1



9-261-ESD-SET1