

Shape	Specification	Tips length	Tips width	Tips thickness	Angle/ Inclined	Ø	Page
straight	with Ø-holder	2.3	1.5 - 3.0			0.8	14
straight	normal	2.5			40°		14
straight	with Ø-holder	5			45°	1.5	14
straight	with Ø-holder	5	4			3.5	14
straight	normal flat	5	6.35				21
straight	normal flat	6	4 - 5	2.6 - 3.8			9, 11
straight	normal flat	6	13	3			14
straight	with Ø-holder	6.5	6			5	14
straight	with Ø-holder	7	6			5	14
straight	normal	8	0.2				9
straight	normal flat	9.5	5	2.8			19
straight	with Ø-holder	10	3.1			2	14
straight	with Ø-holder	10	5.5 - 5.6			5	14
straight	with Ø-holder	10.5	5.8	8			14
straight	normal flat	10.5	5.9	5.5			19
straight	normal flat	20	4	4.5			11
straight	tapered	10		0.5			19
straight	normal	11	3.2				21
straight	normal	12	0.2	0.4			9
straight	copper jaws	11 - 12	4.6 - 6	5.6 - 7.2			14, 19
straight	normal	13	0.65 - 1.0				16, 21
straight	normal	14	3				21
straight	normal	16	2				16
straight	normal	17	1				16
straight	normal	18	3				13
straight	normal	18 Zahnung	3				16
straight	normal	18	4.5				16
straight	interchangeable tip	25	1.8				20
straight	interchangeable tip	26	0.6 - 1.5				20
straight	interchangeable tip	26	1.1 - 2.0				20
straight	interchangeable tip	30	0.7				20
straight	tapered	30	0.1 - 0.5	0.2 - 1.0			7, 12
straight	tapered	35	0.2 - 2.25	0.2 - 1.0			7, 12, 13, 21
straight	tapered	36	2.3	0.4			9, 11
straight	tapered	38	0.4	7			7
straight	normal	42	0.3	0.4			9
straight	normal	45	0.2	0.2			7
straight	normal	46	0.1 - 0.5	0.2 - 1.0			9, 12
straight	normal	48	0.2 - 0.9	0.4 - 1.5			9, 13, 21
straight	normal	50	0.3 - 1.0	0.2 - 0.6			9, 12
straight	normal	50	0.5 - 1.0	0.5 - 0.6			7, 16
straight	normal	53	0.2	0.4			9
straight	normal	54	0.6	1			13
straight	normal	60	0.2	0.4			9
straight	normal	68	0.6	1			9
straight	normal	75	1.3				19
bent	with Ø-holder	2.3	1.5 - 3.0		35°	0.8	14
bent	normal	2.5	1		45°		14
bent	normal	6	6.5	0.7	30°		19
bent	normal flat	10	5		20°		9, 11
bent	normal	10	8	0.5	30°		20
bent	normal	12	2.5		30°		14
bent	tapered	12			16°		21
bent	tapered	14.2			10°		7
bent	tapered	20	4.5		30°		9
bent	interchangeable tip	20		1.6	45°		20
bent	interchangeable tip	25	15	1			20
bent	tapered	27 - 38	7		40°		7, 13
bent	tapered	30	7		30°		7, 11, 12
bent	tapered	34 - 35	14		30°		11
bent	tapered	35	2.3 - 2.6		30°		9, 11
bent	tapered	35	7.4 - 7.5		30°		7
bent	tapered	35	10		50°		7, 12
bent	tapered	40	0.4	0.4			7
bent	normal	45	16	12	60°		13, 16, 19