

Accu-Lube® LB-5000 Micro Metalworking Lubrication System

Accu-Lube® **LB-5000** is a premium performance micro-lubricant designed to be used in conjunction with the Accu-Lube® **Micro-Lubrication system**. It is formulated from unique blend of highly refined natural base oils to provide “near dry” machining operations. Accu-Lube® LB-5000 is suitable for light to medium duty cutting operations on non-ferrous materials.

The Accu-Lube® **Micro-Lubrication system** is a revolutionary approach to regulating the supply of lubricant to the cutting zone. The precisely controlled delivery maximises cutting tool performance whilst minimising fluid usage and reducing costs.

Features

- Cleaner machining operations - reduced degreasing costs.
- Reduced fluid consumption.
- Manufactured from renewable sources.
- Natural base - non irritating, non toxic.
- Contains no - Biocide, Sulphur, Nitrite and Chlorine.
- No waste disposal.
- Improved tool life.
- No component staining.

Applications

- General machining and sawing of non-ferrous materials.
- Requires No cleaning off prior to heat treating.

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance
of our products, for which reason it is given without responsibility.

Technical Data

ROCOL®

Performance you can trust

Accu-Lube® LB-5000

Appearance	Clear blue liquid
Odour	Mild
Viscosity at 40°C	19cSt
Density at 20°C	0.85 g/cm ³
Storage	Store at normal ambient temperature (15 to 30°C)
Pack Sizes – Part Codes	5 ltr - 74036 200 ltr - 74039

Date: Apr-09

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67

Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance
of our products, for which reason it is given without responsibility.