

Technical Data



Performance you can trust

FOODLUBE® Seamer Fluid 150



ISO 21469 Certified

High performance, ISO VG 150, food grade fluid for can seamers

Product Overview

ROCOL® FOODLUBE Seamer Fluid 150 is a non-toxic can seamer lubricant which is supplied with a viscosity grade of ISO VG 150.

ROCOL FOODLUBE Seamer Fluid 150 is designed specifically for the lubrication of can seamers operating with either total loss or recirculating lubrication systems.

ROCOL FOODLUBE Seamer Fluid 150 is a tenacious, extreme pressure (EP), synthetic oil containing additives to boost performance, improve adhesion and provide excellent corrosion protection.

It is ideal for use in food, pharmaceutical and other clean environments where NSF H1 lubricants are required.

Features and Benefits

- FOODLUBE Seamer Fluid 150 offers excellent wide temperature resistance of -20°C to +150°C.
- FOODLUBE Seamer Fluid 150 has outstanding EP performance.
- FOODLUBE Seamer Fluid 150 provides a tenacious, EP film with excellent water wash-off resistance and corrosion protection.
- FOODLUBE Seamer Fluid 150 has excellent stability resulting in extended relubrication intervals and a reduction in lubricant usage.

Directions for Storage and Use

- For optimum performance drain & flush prior to filling with Rocol FOODLUBE Seamer Fluid 150.
- When using FOODLUBE Seamer Fluid 150 in a recirculating system ensure that the oil filters are renewed during an oil change.
- The storage temperature of Rocol FOODLUBE Seamer Fluid 150 should be controlled between +1°C and +40°C.
- Shelf life is 3 years from date of manufacture.

Specifications

- FOODLUBE Seamer Fluid 150 does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- FOODLUBE Seamer Fluid 150 is manufactured from only FDA listed ingredients: FDA Group 21 CFR 178.3570
- NSF H1 registered – 143579
- ISO 21469
- Halal certified
- Kosher certified

Pack Sizes

| Pack Size | Part Code |
|-----------|-----------|
| 200L | 16029 |

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of Ltd



FM 12448



EMS 67596



OHS 78173



Technical Data



Performance you can trust



ISO 21469 Certified

FOODLUBE® Seamer Fluid 150

High performance, ISO VG 150, food grade fluid for can seamers

| Property | Test Method | Result |
|--------------------|------------------|--|
| Appearance | Visual | Pale yellow, almost colourless, liquid |
| Base Type | N/A | Polyalphaolefin |
| Viscosity at 40°C | IP71 – ASTM D445 | 150cSt |
| Viscosity at 100°C | IP71 – ASTM D445 | 16.8cSt |
| Viscosity index | IP71 – ASTM D445 | 121 |
| Temperature Range | N/A | -20°C to +150°C |

Values quoted above are typical and do not constitute a specification.

FOODLUBE Seamer Fluid 150 is produced at a Halal Control Certified Site (Swillington UK) and is certified as Halal only where the Halal Control Logo is displayed on the product label (certificate registration number C-912-350-05-01/1).

Safety Data Sheets

Safety data sheets are available for download from our website www.rocol.com or may be obtained from your usual ROCOL contact.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Issue: 4 Date: 10-17

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com
ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of Ltd



FM 12448



EMS 67596



OHS 78173

