

METALFLO 4000

Water Based Graphite Dispersion

METALFLO 4000 is a water based graphite dispersion for use in the hot metal working industries. ROCOL METALFLO 4000 is particularly suitable for drop hammer and press forging.

METALFLO 4000 is used for the lubrication of all types of hot metal working tools including press and drop hammer dies. METALFLO 4000 is formulated for application through manual or automatic systems and is recommended for use over a wide range of billet weight and component complexity. Suitable for die temperatures up to, and in excess of 400°C.

Features

- Fume free.
- Aids metal flow - promotes die filling.
- Minimum carry over on non-ferrous metals.
- Controls die temperature and extends die life.
- Forms an even bonded coating on hot metal surfaces.

Directions for Use

METALFLO 4000 can be used neat or diluted with up to 20 parts water depending on severity of operation. It can be applied manually but for best results it is recommended that an automatic spray system is used.

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Technical Data

ROCOL®

Performance you can trust

METALFLO 4000

Appearance	Grey/black liquid
Carrier	Water
Graphite Content	17.5%
Particle Size	50% below 2 microns
Viscosity at 25°C	1747 cSt
Specific Gravity	1.13
Storage	Store at normal ambient temperature, 0°C to 40°C. Do not freeze.
Pack Sizes – Part Codes	20 litre - 78543

Date: Jan-09

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67

Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers .
There are many factors outside our control or knowledge which affect the use and performance
of our products, for which reason it is given without responsibility.