

Technical Data

UltraSpin 10

High Speed Spindle Bearing Lubricant

Description

UltraSpin 10 has been designed for all types of spindle bearings, including high speed.

UltraSpin 10 has been formulated for high oxidation stability, corrosion, and wear protection.

UltraSpin 10 contains a pour point depressant, allowing the oil to flow at very low temperatures, preventing wax crystallization in the oil.

Features & Benefits

- Good oxidation stability leading to a longer operating life and reduction in deposit formation.
- Contains an additive package which provides an excellent corrosion protection of steel.
- Pour point depressant to allow to flow during low temperatures.

Directions For Use

- UltraSpin 10 should be stored in its unopened original container.
- Storage temperature should be controlled to between +1°C and +40°C.
- Shelf life is 5 years from date of manufacture

Further Information

For pack sizes, part codes and safety data sheets please visit www.rocol.com or get in touch with our customer service team who will be happy to help: customer.service@rocol.com

Property	Test Method	Result
Appearance	N/A	Amber Liquid
Four Ball Wear Scar (mm)	ASTM D-4172	0.679
Viscosity @ 40°C (cSt)	ASTM D2270-10	10.5
Viscosity @ 100°C (cSt)	ASTM D2270-10	2.86
Density (g/cm3)	ASTM D4052-18a	0.8867

Values above are typical and do not constitute a specification

Issue 2 Date: 06/22

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740
 E customer.service@rocol.com www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.

ROCOL® A division of  Ltd

