

Technical Data

ROCOL®

Performance you can trust

ULTRAFORM™ 1050 High Performance Low Viscosity Cold Metal Forming Lubricant

ULTRAFORM™ 1050 is a high performance, light viscosity cold metal forming lubricant, suitable for use with a wide range of ferrous and non-ferrous metals including a range of galvanized and zintec coated steels.

ULTRAFORM™ 1050 contains extreme pressure additives which prevent metal pick up between the work piece and tool and provide a cost effective route to increased production rates.

ULTRAFORM™ 1050 works as a vanishing film, eliminating the need to degrease components in some circumstances.

Features

- Minimises “slug pulling” on thin gauge materials.
- Vanishing film.
- Reduces metal pick up and scoring.
- Easily cleaned.

Directions for Use

ULTRAFORM™ 1050 may be applied by brush, drip, roller, aerospray, or airless spray systems.

Where absolute freedom from surface discolouration is essential, it is recommended that compatibility trials are performed.

Appearance	Straw liquid
Odour	Mild
Kinematic Viscosity	5.5 cSt at 25°C
Density at 20°C	0.80 g/cm ³
Storage	Store at normal ambient temperature (5 to 30°C)
Pack Sizes – Part Codes	20 ltr - 86103 200 ltr - 86109

Date: Jan-09

T +44 (0) 113 232 2600

F +44 (0) 113 232 2740

E customer-service@rocol.com

www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67

Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.